



CE 系列 3 相高压防爆电动机主要尺寸

主要尺寸

C	MOUL		E	
	Basic size	Limit deviation	Basic size	Limit deviation
254	±4	140	±0.5	20
280	±4	210	±0.57	28
425	±4	170	±0.5	22
315	±4	210	±0.57	28
530	±4	170	±0.5	25
355	±4	210	±0.57	32
		250		36
		210		32
		300		36
			±0.65	40



PERFORMANCE DATA
YX3 SERIES HIGH-VOLTAGE 3-PHASE INDUCTION MOTORS (3kV)

YX3

性能指标


YX3-560-2	1600	180.6	2985	96.9	0.88	0.7	7	2
-560-2	1800	202.9	2985	97.0	0.88	0.7	7	2
-560-2	2000	222.7	2985	97.1	0.89	0.7	7	2
-630-2	2240	249.2	2985	97.2	0.89	0.7	7	2
-630-2	2500	278.1	2985	97.2	0.89	0.7	7	2
-630-2	2800	311.1	2985	97.3	0.89	0.7	7	2
-355-4	100	22.7	1488	94.5	0.83	0.8	6.5	2
355-4	200	24.5	1488	94.6	0.83	0.8	6.5	2
355-4	220	26.9	1488	94.7	0.83	0.8	6.5	2
355-4	250	30.6	1488	94.8	0.83	0.8	6.5	2
355-4	280	34.2	1488	94.9	0.83	0.8	6.5	2
355-4	315	38.0	1488	95	0.84	0.8	6.5	2
355-4	355	42.7	1488	95.2	0.84	0.8	6.5	2
355-4	400	48.1	1488	95.3	0.84	0.8	6.5	2



PERFORMANCE DATA

YX3 SERIES HIGH-VOLTAGE 3-PHASE INDUCTION MOTORS (6kV)

Type	Output kW	Rated Current A	Rated speed r/min	Efficiency %	Power Factor COSΦ	TST/Tn	IST/In	TM/Tn
YX3-500-6	1120	134.6	987	96.5	0.83	0.8	6	2
YX3-560-6	1250	150.0	987	96.6	0.83	0.7	6	2
YX3-560-6	1400	163.9	987	96.7	0.85	0.7	6	2
YX3-560-6	1600	187.1	987	96.8	0.85	0.7	6	2
YX3-560-6	1800	210.3	987	96.9	0.85	0.7	6	2
YX3-560-6	2000	233.4	987	97	0.85	0.7	6	2
YX3-630-6	2240	261.4	987	97	0.85	0.7	6	2
YX3-630-6	2500	291.5	987	97.1	0.85	0.7	6	2
YX3-355-8	185	25.2	742	94.3	0.75	0.8	5.5	2
YX3-355-8	200	26.8	742	94.4	0.76	0.8	5.5	2
YX3-355-8	220	29.5	742	94.5	0.76	0.8	5.5	2
YX3-355-8	250	33.0	742	94.6	0.77	0.8	5.5	2
YX3-400-8	280	36.9	742	94.8	0.77	0.8	5.5	2
YX3-400-8	315	41.5	742	94.9	0.77	0.8	5.5	2
YX3-400-8	355	46.7	742	95	0.77	0.8	5.5	2
YX3-400-8	400	51.8	742	95.2	0.78	0.8	5.5	2
YX3-450-8	450	58.3	742	95.3	0.78	0.8	5.5	2
YX3-450-8	500	63.7	742	95.6	0.79	0.8	5.5	2
YX3-450-8	560	71.3	742	95.7	0.79	0.8	5.5	2
YX3-500-8	630	79.1	742	95.8	0.8	0.8	5.5	2
YX3-500-8	710	89.1	742	95.9	0.8	0.8	5.5	2
YX3-500-8	800	100.2	742	96	0.8	0.8	5.5	2
YX3-560-8	900	112.6	742	96.1	0.8	0.7	5.5	2
YX3-560-8	1000	123.5	742	96.2	0.81	0.7	5.5	2
YX3-560-8	1120	138.2	742	96.3	0.81	0.7	5.5	2
YX3-560-8	1250	154.2	742	96.3	0.81	0.7	5.5	2
YX3-560-8	1400	172.5	742	96.4	0.81	0.7	5.5	2
YX3-630-8	1600	197.0	742	96.5	0.81	0.7	6	2
YX3-630-8	1800	218.7	742	96.6	0.82	0.7	6	2
YX3-630-8	2000	242.7	742	96.7	0.82	0.7	6	2
YX3-630-8	2240	271.6	742	96.8	0.82	0.7	6	2
YX3-400-10	185	25.3	595	93.7	0.75	0.7	5.5	1.8
YX3-400-10	200	27.0	595	93.9	0.76	0.7	5.5	1.8
YX3-400-10	220	29.6	595	94	0.76	0.7	5.5	1.8
YX3-400-10	250	33.6	595	94.1	0.76	0.7	5.5	1.8




4

■ ■

YX3-560-10	1000	125.4	595	95.8	0.8	0.7	5.5	1.8
YX3-560-10	1120	140.3	595	95.9	0.8	0.7	5.5	1.8
YX3-630-10	1250	156.3	595	96	0.8	0.7	5.5	1.8
YX3-630-10	1400	172.7	595	96.2	0.81	0.7	6	1.8
YX3-630-10	1600	197.4	595	96.3	0.81	0.7	6	1.8
YX3-630-10	1800	221.8	595	96.4	0.81	0.7	6	1.8
YX3-450-12	220	31.9	495	93.5	0.71	0.7	5.5	1.8
YX3-450-12	250	36.2	495	93.7	0.71	0.7	5.5	1.8
YX3-450-12	280	40.2	495	94.4	0.71	0.7	5.5	1.8
YX3-450-12	315	45.1	495	94.6	0.71	0.7	5.5	1.8
YX3-500-12	355	50.8	495	94.7	0.71	0.7	5.5	1.8
YX3-500-12	400	54.1	495	94.9	0.75	0.7	5.5	1.8
YX3-500-12	450	60.8	495	95	0.75	0.7	5.5	1.8
YX3-500-12	500	67.4	495	95.2	0.75	0.7	5.5	1.8





产品型号	规格	数量	单价	合计	占比	备注
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	
Y2-200L-4	3000W	100	3000.00	3000.00	1.07%	



PERFORMANCE DATA

YX3 SERIES HIGH-VOLTAGE 3-PHASE INDUCTION MOTORS (10kV)

Type	Output kW	Rated Current A	Rated speed r/min	Efficiency %	Power Factor COSΦ	TST/Tn	IST/In	TM/Tn
YX3-560-6	1250	90.0	987	96.6	0.83	0.7	6	2
YX3-560-6	1400	100.6	987	96.8	0.83	0.7	6	2
YX3-560-6	1550	111.2	987	96.9	0.83	0.7	6	2
YX3-560-6	1700	121.8	987	97.0	0.83	0.7	6	2
YX3-560-6	1850	132.4	987	97.1	0.83	0.7	6	2
YX3-560-6	2000	143.0	987	97.2	0.83	0.7	6	2
YX3-560-6	2200	157.6	987	97.3	0.83	0.7	6	2
YX3-560-6	2400	172.2	987	97.4	0.83	0.7	6	2
YX3-560-6	2600	186.8	987	97.5	0.83	0.7	6	2
YX3-560-6	2800	201.4	987	97.6	0.83	0.7	6	2
YX3-560-6	3000	216.0	987	97.7	0.83	0.7	6	2
YX3-560-6	3200	230.6	987	97.8	0.83	0.7	6	2
YX3-560-6	3400	245.2	987	97.9	0.83	0.7	6	2
YX3-560-6	3600	259.8	987	98.0	0.83	0.7	6	2
YX3-560-6	3800	274.4	987	98.1	0.83	0.7	6	2
YX3-560-6	4000	289.0	987	98.2	0.83	0.7	6	2
YX3-560-6	4200	303.6	987	98.3	0.83	0.7	6	2
YX3-560-6	4400	318.2	987	98.4	0.83	0.7	6	2
YX3-560-6	4600	332.8	987	98.5	0.83	0.7	6	2
YX3-560-6	4800	347.4	987	98.6	0.83	0.7	6	2
YX3-560-6	5000	362.0	987	98.7	0.83	0.7	6	2
YX3-560-6	5200	376.6	987	98.8	0.83	0.7	6	2
YX3-560-6	5400	391.2	987	98.9	0.83	0.7	6	2
YX3-560-6	5600	405.8	987	99.0	0.83	0.7	6	2
YX3-560-6	5800	420.4	987	99.1	0.83	0.7	6	2
YX3-560-6	6000	435.0	987	99.2	0.83	0.7	6	2
YX3-560-6	6200	449.6	987	99.3	0.83	0.7	6	2
YX3-560-6	6400	464.2	987	99.4	0.83	0.7	6	2
YX3-560-6	6600	478.8	987	99.5	0.83	0.7	6	2
YX3-560-6	6800	493.4	987	99.6	0.83	0.7	6	2
YX3-560-6	7000	508.0	987	99.7	0.83	0.7	6	2
YX3-560-6	7200	522.6	987	99.8	0.83	0.7	6	2
YX3-560-6	7400	537.2	987	99.9	0.83	0.7	6	2
YX3-560-6	7600	551.8	987	100.0	0.83	0.7	6	2
YX3-560-6	7800	566.4	987	100.1	0.83	0.7	6	2
YX3-560-6	8000	581.0	987	100.2	0.83	0.7	6	2
YX3-560-6	8200	595.6	987	100.3	0.83	0.7	6	2
YX3-560-6	8400	610.2	987	100.4	0.83	0.7	6	2
YX3-560-6	8600	624.8	987	100.5	0.83	0.7	6	2
YX3-560-6	8800	639.4	987	100.6	0.83	0.7	6	2
YX3-560-6	9000	654.0	987	100.7	0.83	0.7	6	2
YX3-560-6	9200	668.6	987	100.8	0.83	0.7	6	2
YX3-560-6	9400	683.2	987	100.9	0.83	0.7	6	2
YX3-560-6	9600	697.8	987	101.0	0.83	0.7	6	2
YX3-560-6	9800	712.4	987	101.1	0.83	0.7	6	2
YX3-560-6	10000	727.0	987	101.2	0.83	0.7	6	2
YX3-560-6	10200	741.6	987	101.3	0.83	0.7	6	2
YX3-560-6	10400	756.2	987	101.4	0.83	0.7	6	2
YX3-560-6	10600	770.8	987	101.5	0.83	0.7	6	2
YX3-560-6	10800	785.4	987	101.6	0.83	0.7	6	2
YX3-560-6	11000	800.0	987	101.7	0.83	0.7	6	2
YX3-560-6	11200	814.6	987	101.8	0.83	0.7	6	2
YX3-560-6	11400	829.2	987	101.9	0.83	0.7	6	2
YX3-560-6	11600	843.8	987	102.0	0.83	0.7	6	2
YX3-560-6	11800	858.4	987	102.1	0.83	0.7	6	2
YX3-560-6	12000	873.0	987	102.2	0.83	0.7	6	2
YX3-560-6	12200	887.6	987	102.3	0.83	0.7	6	2
YX3-560-6	12400	902.2	987	102.4	0.83	0.7	6	2
YX3-560-6	12600	916.8	987	102.5	0.83	0.7	6	2
YX3-560-6	12800	931.4	987	102.6	0.83	0.7	6	2
YX3-560-6	13000	946.0	987	102.7	0.83	0.7	6	2
YX3-560-6	13200	960.6	987	102.8	0.83	0.7	6	2
YX3-560-6	13400	975.2	987	102.9	0.83	0.7	6	2
YX3-560-6	13600	989.8	987	103.0	0.83	0.7	6	2
YX3-560-6	13800	1004.4	987	103.1	0.83	0.7	6	2
YX3-560-6	14000	1019.0	987	103.2	0.83	0.7	6	2
YX3-560-6	14200	1033.6	987	103.3	0.83	0.7	6	2
YX3-560-6	14400	1048.2	987	103.4	0.83	0.7	6	2
YX3-560-6	14600	1062.8	987	103.5	0.83	0.7	6	2
YX3-560-6	14800	1077.4	987	103.6	0.83	0.7	6	2
YX3-560-6	15000	1092.0	987	103.7	0.83	0.7	6	2
YX3-560-6	15200	1106.6	987	103.8	0.83	0.7	6	2
YX3-560-6	15400	1121.2	987	103.9	0.83	0.7	6	2
YX3-560-6	15600	1135.8	987	104.0	0.83	0.7	6	2
YX3-560-6	15800	1150.4	987	104.1	0.83	0.7	6	2
YX3-560-6	16000	1165.0	987	104.2	0.83	0.7	6	2
YX3-560-6	16200	1179.6	987	104.3	0.83	0.7	6	2
YX3-560-6	16400	1194.2	987	104.4	0.83	0.7	6	2
YX3-560-6	16600	1208.8	987	104.5	0.83	0.7	6	2
YX3-560-6	16800	1223.4	987	104.6	0.83	0.7	6	2
YX3-560-6	17000	1238.0	987	104.7	0.83	0.7	6	2
YX3-560-6	17200	1252.6	987	104.8	0.83	0.7	6	2
YX3-560-6	17400	1267.2	987	104.9	0.83	0.7	6	2
YX3-560-6	17600	1281.8	987	105.0	0.83	0.7	6	2
YX3-560-6	17800	1296.4	987	105.1	0.83	0.7	6	2
YX3-560-6	18000	1311.0	987	105.2	0.83	0.7	6	2
YX3-560-6	18200	1325.6	987	105.3	0.83	0.7	6	2
YX3-560-6	18400	1340.2	987	105.4	0.83	0.7	6	2
YX3-560-6	18600	1354.8	987	105.5	0.83	0.7	6	2
YX3-560-6	18800	1369.4	987	105.6	0.83	0.7	6	2
YX3-560-6	19000	1384.0	987	105.7	0.83	0.7	6	2
YX3-560-6	19200	1398.6	987	105.8	0.83	0.7	6	2
YX3-560-6	19400	1413.2	987	105.9	0.83	0.7	6	2
YX3-560-6	19600	1427.8	987	106.0	0.83	0.7	6	2
YX3-560-6	19800	1442.4	987	106.1	0.83	0.7	6	2
YX3-560-6	20000	1457.0	987	106.2	0.83	0.7	6	2
YX3-560-6	20200	1471.6	987	106.3	0.83	0.7	6	2
YX3-560-6	20400	1486.2	987	106.4	0.83	0.7	6	2
YX3-560-6	20600	1500.8	987	106.5	0.83	0.7	6	2
YX3-560-6	20800	1515.4	987	106.6	0.83	0.7	6	2
YX3-560-6	21000	1530.0	987	106.7	0.83	0.7	6	2
YX3-560-6	21200	1544.6	987	106.8	0.83	0.7	6	2
YX3-560-6	21400	1559.2	987	106.9	0.83	0.7	6	2
YX3-560-6	21600	1573.8	987	107.0	0.83	0.7	6	2
YX3-560-6	21800	1588.4	987	107.1	0.83	0.7	6	2
YX3-560-6	22000	1603.0	987	107.2	0.83	0.7	6	2
YX3-560-6	22200	1617.6	987	107.3	0.83	0.7	6	2
YX3-560-6	22400	1632.2	987	107.4	0.83	0.7	6	2
YX3-560-6	22600	1646.8	987	107.5	0.83	0.7	6	2
YX3-560-6	22800	1661.4	987	107.6	0.83	0.7	6	2
YX3-560-6	23000	1676.0	987	107.7	0.83	0.7	6	2
YX3-560-6	23200	1690.6	987	107.8	0.83	0.7	6	2
YX3-560-6	23400	1705.2	987	107.9	0.83	0.7	6	2
YX3-560-6	23600	1719.8	987	108.0	0.83	0.7	6	2
YX3-560-6	23800	1734.4	987	108.1	0.83	0.7	6	2
YX3-560-6	24000	1749.0	987	108.2	0.83	0.7	6	2
YX3-560-6	24200	1763.6	987	108.3	0.83	0.7	6	2
YX3-560-6	24400	1778.2	987	108.4	0.83	0.7	6	2
YX3-560-6	24600	1792.8	987	108.5	0.83	0.7	6	2
YX3-560-6	24800	1807.4	987	108.6	0.83	0.7	6	2
YX3-560-6	25000	1822.0	987	108.7	0.83	0.7	6	2
YX3-560-6	25200	1836.6	987	108.8	0.83	0.7	6	2
YX3-560-6	25400	1851.2	987	108.9	0.83	0.7	6	2
YX3-560-6	25600	1865.8	987	109.0	0.83	0.7	6	2
YX3-560-6	25800	1880.4	987	109.1	0.83	0		

PERFORMANCE DATA

YV2 系列三相异步电动机主要性能指标数据表 (续)

续前表:

续前表

YV2 300-12	600	12.9	195	93.1	0.71	0.7	0	1.8
YV2 300-12	630	16.8	195	93.2	0.71	0.7	0	1.8
YV2 300-12	710	20.5	195	93.5	0.71	0.7	0	1.8
YV2 300-12	800	28.0	195	93.7	0.71	0.7	0	1.8
YV2 300-12	900	35.5	195	93.7	0.71	0.7	0	1.8
YV2 300-12	1000	43.8	195	93.7	0.72	0.7	0	1.8
YV2 300-12	1100	52.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1200	61.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1300	70.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1400	79.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1500	88.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1600	98.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1700	108.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1800	118.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	1900	128.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2000	138.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2100	149.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2200	160.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2300	171.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2400	182.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2500	193.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2600	205.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2700	217.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2800	229.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	2900	241.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3000	253.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3100	266.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3200	279.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3300	292.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3400	305.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3500	318.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3600	332.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3700	346.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3800	360.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	3900	374.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4000	388.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4100	403.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4200	418.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4300	433.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4400	448.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4500	463.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4600	479.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4700	495.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4800	511.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	4900	527.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5000	543.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5100	560.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5200	577.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5300	594.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5400	611.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5500	628.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5600	646.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5700	664.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5800	682.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	5900	700.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6000	718.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6100	737.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6200	756.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6300	775.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6400	794.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6500	813.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6600	833.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6700	853.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6800	873.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	6900	893.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7000	913.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7100	934.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7200	955.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7300	976.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7400	997.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7500	1018.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7600	1040.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7700	1062.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7800	1084.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	7900	1106.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8000	1128.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8100	1151.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8200	1174.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8300	1197.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8400	1220.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8500	1243.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8600	1267.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8700	1291.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8800	1315.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	8900	1339.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9000	1363.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9100	1388.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9200	1413.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9300	1438.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9400	1463.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9500	1488.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9600	1514.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9700	1540.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9800	1566.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	9900	1592.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10000	1618.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10100	1645.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10200	1672.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10300	1699.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10400	1726.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10500	1753.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10600	1781.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10700	1809.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10800	1837.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	10900	1865.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11000	1893.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11100	1922.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11200	1951.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11300	1980.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11400	2009.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11500	2038.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11600	2068.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11700	2098.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11800	2128.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	11900	2158.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12000	2188.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12100	2219.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12200	2250.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12300	2281.2	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12400	2312.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12500	2343.8	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12600	2375.4	195	93.8	0.72	0.7	0	1.8
YV2 300-12	12700	2407.2	195	93.8	0.72	0.7	0	1